

# DesignLights Consortium



Model Number	ALI-IP55-4FT-40W-65K-MILKY
Classification	Standard
Primary Use	Low-Bay Luminaires for Commercial and Industrial Buildings
Reported Input Wattage	40 W
Reported Light Output	5000 lm
Reported CCT	6500 K
Reported CRI (Ra)	80
Product ID	S-LU5RS8
DLC Family Code	<a href="#">ZZZFRO</a>
Listing Status	Listed
Date Qualified	2023-05-26

## PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-LU5RS8
Manufacturer	Shenzhen BMMQ Technology Co., Ltd.
Brand	Shenzhen BMMQ Technology Co., Ltd
Model Number	ALI-IP55-4FT-40W-65K-MILKY
Parent	No
Classification	Standard
DLC Family Code	ZZZFRO
Input Power Type	AC

## PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	Low-Bay
Primary Use Designation	Low-Bay Luminaires for Commercial and Industrial Buildings

## CONTROL FEATURES VIEW DETAILS

Integral Controls	No
-------------------	----

Dimming Capability and Range	Continuous Dimming above 10%
Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

## REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	5000 lm
Reported Efficacy (AC)	125 lm/W
Reported CCT	6500 K
Reported CRI (Ra)	80
Reported R9	1
Reported IES Rf	83
Reported IES Rg	97
Reported IES Rcs,h1	-13
Reported Default Light Output	5000 lm

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	40 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Default Input Wattage	40 W
Voltage Range	100-277 V

## VERSION HISTORY VIEW DETAILS

2023-05-26	Listed	5.1	Standard
------------	--------	-----	----------