DesignLights Consortium





ClassificationStandardPrimary UseInternal Driver/Line Voltage (UL Type B) LampsReported Input Wattage12 WReported Light Output2112 ImReported CCT4000 KReported CRI (Ra)80Product IDS-5P9JYODLC Family CodeJJJOVAListedListed	1	
Primary UseInternal Driver/Line Voltage (UL Type B) LampsReported Input Wattage12 WReported Light Output2112 ImReported CCT4000 KReported CRI (Ra)80Product IDS-5P9JYODLC Family CodeJJJOVAListing StatusListed	Model Number	T8-ER120B-F12W-B 4000K
Reported Input Wattage12 WReported Light Output2112 ImReported CCT4000 KReported CRI (Ra)80Product IDS-5P9JYODLC Family CodeJJJOVAListing StatusListed	Classification	Standard
Reported Light Output2112 ImReported CCT4000 KReported CRI (Ra)80Product IDS-5P9JYODLC Family CodeJJJOVAListing StatusListed	Primary Use	Internal Driver/Line Voltage (UL Type B) Lamps
Reported CCT4000 KReported CRI (Ra)80Product IDS-5P9JYODLC Family CodeJJJOVAListing StatusListed	Reported Input Wattage	12 W
Reported CRI (Ra)80Product IDS-5P9JYODLC Family CodeJJJOVAListing StatusListed	Reported Light Output	2112 lm
Product ID S-5P9JYO DLC Family Code JJJOVA Listing Status Listed	Reported CCT	4000 K
DLC Family Code JJJOVA Listing Status Listed	Reported CRI (Ra)	80
Listed	Product ID	S-5P9JYO
	DLC Family Code	AVOLL
Date Qualified 2022-11-16	Listing Status	Listed
	Date Qualified	2022-11-16

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-5P9JYO
Manufacturer	Shenzhen BMMQ Technology Co., Ltd.
Brand	BMMQ
Model Number	T8-ER120B-F12W-B 4000K
Parent	No
Classification	Standard
DLC Family Code	JJJOVA
Length	4.0 ft
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Linear Replacement Lamp
General Application	T8 Four-Foot
Primary Use Designation	Internal Driver/Line Voltage (UL Type B) Lamps

CONTROL FEATURES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	Phase Cut
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Beam Angle	140 °
Reported Light Output	2112 lm
Reported Efficacy (AC)	176 lm/W
Reported CCT	4000 K
Reported CRI (Ra)	80
Reported R9	8
Reported IES Rf	84
Reported IES Rg	97
Reported IES Rcs,h1	-11
Reported Default Light Output	2112 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	12 W
Reported Total Harmonic Distortion	15 %
Reported Power Factor	0.9
Reported Default Input Wattage	12 W
Voltage Range	100-277 V

VERSION HISTORY VIEW DETAILS

2022-11-16	Listed	5.1	Standard
------------	--------	-----	----------