

DesignLights Consortium



Model Number	TS-WP07-45W/60W/75W-H-TCP
Classification	Premium
Primary Use	Outdoor Full-Cutoff Wall-Mounted Area Luminaires
Reported Input Wattage	71.8 W
Reported Light Output	8749 lm
Reported CCT	3000 K
Reported CRI (Ra)	84
Product ID	PIEC1YS4
DLC Family Code	DDDLPU
Listing Status	Listed
Date Qualified	2021-11-23

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PIEC1YS4
Manufacturer	Torshare Ltd
Brand	TORSHARE
Model Number	TS-WP07-45W/60W/75W-H-TCP
Parent	Yes
Classification	Premium
DLC Family Code	DDDLPU
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires
General Application	Mid Output
Primary Use Designation	Outdoor Full-Cutoff Wall-Mounted Area Luminaires

CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	Exterior Photocell
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	8749 lm
Reported Efficacy (AC)	121.94 lm/W
Reported CCT	3000 K
Reported CRI (Ra)	84
Reported R9	14
Reported IES Rf	85
Reported IES Rg	97
Reported IES Rcs,h1	-11
Reported Minimum Light Output	5400 lm
Reported Maximum Light Output	8749 lm
Reported Minimum CCT	3000 K
Reported Maximum CCT	5000 K
Reported Default Light Output	8749 lm
Reported BUG Rating	B2 U2 G1

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	71.8 W
Reported Total Harmonic Distortion	12.4 %
Reported Power Factor	0.965
Reported Minimum Input Wattage	45 W
Reported Maximum Input Wattage	71.8
Reported Default Input Wattage	71.8 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Voltage for Minimum Efficacy	120
Tested Light Output	8749 lm
Tested Efficacy (AC)	121.94 lm/W
Tested CCT	3042 K
Tested CRI (Ra)	84
Tested R9	14
Tested IES Rf	86
Tested IES Rg	97
Tested IES Rcs,h1	-11 %
Tested Duv	-0.0012
Tested Backlight (TM-15 BUG)	2
Tested BUG Rating	B2 U2 G1

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Input Wattage	71.8 W
Tested Total Harmonic Distortion	12.5 %
Tested Power Factor	0.964

VERSION HISTORY VIEW DETAILS

2021-11-23	Listed	5.1	Premium
------------	--------	-----	---------